



DSA SERIES

Load Life : 60°C 2000hours

◆ **FEATURES**


- Low Resistance
- RoHS compliance




◆ **SPECIFICATIONS**

Items	Characteristics
Category Temperature Range	-25~+60°C
Rated Voltage Range	2.5V.DC
Capacitance Tolerance	±20%(20°C)
Characteristics at High and low Temperatures	Capacitance Change $ \Delta C/C(+20^\circ C) \leq 30\%$
	DC Internal Resistance Max, 6 times of value at +20°C (at -25°C)
Endurance	After 2000 hours with rated voltage at 60°C, the capacitors shall meet the following requirements.
	Capacitance Change $ \Delta C/C(\text{initial}) \leq 30\%$
Storage at High Temperature	DC Internal Resistance Max, 3 times of the specification
	After 2000 hours without load at 60°C, the capacitors shall meet the same requirements specified for endurance.

◆ **PART NUMBER**



◆ **DIMENSIONS**



◆ **STANDARD SIZE**

Rated Voltage (V.DC)	Rated Capacitance (F)	DC Internal Resistance (mΩ)	φ D×L (mm)	Part No.
2.5	850	4	36×135	2.5DSA850□36×135
	1900	2	51×135	2.5DSA1900□51×135

□:Tolerance(M:±20)