



EMIF03-SIM02F3

3-line IPAD™, EMI filter including ESD protection

Features

- EMI symmetrical (I/O) low-pass filter
- High efficiency in EMI filtering
- Lead-free package
- Very low PCB space occupation: 1.2 mm²
- Very thin package: 0.60 mm
- High efficiency in ESD suppression
- High reliability offered by monolithic integration
- High reduction of parasitic elements through integration and wafer level packaging

Complies with the following standards:

- IEC 61000-4-2 Level 4 on external and V_{cc} pins:
 - 15 kV (air discharge)
 - 8 kV (contact discharge)
- Level 1 on internal pins:
 - 2 kV (air discharge)
 - 2 kV (contact discharge)
- MIL STD 883E - Method 3015-6 Class 3

Applications

EMI filtering and ESD protection for:

- SIM interface (subscriber identity module)
- UIM interface (universal identity module)

Description

The EMIF03-SIM02F3 is a highly integrated device designed to suppress EMI/RFI noise in all systems subjected to electromagnetic interference.

This filter includes ESD protection circuitry which prevents damage to the protected device when subjected to ESD surges up to 15 kV.




Figure 1. Pin layout (bump side)





Figure 2. Device configuration



TM: IPAD is a trademark of STMicroelectronics.

1 Characteristics

Table 1. Absolute maximum ratings ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Symbol	Parameter and test conditions	Value	Unit
V_{PP}	Internal pins (A3, B3, C3):		
	ESD discharge IEC61000-4-2, air discharge	2	kV
	ESD discharge IEC61000-4-2, contact discharge	2	
	External pins (A2, B1, C2, C1):		
ESD discharge IEC61000-4-2, air discharge	15		
	ESD discharge IEC61000-4-2, contact discharge	8	
T_j	Maximum junction temperature	125	$^{\circ}\text{C}$
T_{op}	Operating temperature range	-40 to +85	$^{\circ}\text{C}$
T_{stg}	Storage temperature range	-55 to 150	$^{\circ}\text{C}$

Table 2. Electrical characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$)

Symbol	Parameters				
V_{BR}	Breakdown voltage				
I_{RM}	Leakage current @ V_{RM}				
V_{RM}	Stand-off voltage				
V_{CL}	Clamping voltage				
I_{PP}	Peak pulse current				
$R_{I/O}$	Series resistance between input and output				
C_{line}	Input capacitance per line				
Symbol	Test conditions	Min	Typ	Max	Unit
V_{BR}	$I_R = 1\text{ mA}$	6		20	V
I_{RM}	$V_{RM} = 3\text{ V}$			0.2	μA
R_d			1.5		Ω
R_1, R_3	Tolerance $\pm 20\%$		100		Ω
R_2	Tolerance $\pm 20\%$		47		Ω
C_{line}	$V_{line} = 0\text{ V}, V_{osc} = 30\text{ mV}, F = 1\text{ MHz}$			20	pF

Figure 3. S21 (dB) attenuation measurement (A2-A3 line)




Figure 4. S21 (dB) attenuation measurement (B1-B3 line)




Figure 5. S21 (dB) attenuation measurement (C1-C3 line)




Figure 6. Analog crosstalk measurement




Figure 7. Digital crosstalk measurement




Figure 8. Line capacitance versus reverse applied voltage (typical)




Figure 9. Voltages when IEC 61000-4-2 (+15 kV air discharge) applied to external pin





Figure 10. Voltages when IEC 61000-4-2 (- 15 kV air discharge) applied to external pin



KTTIC

2 Application information

Figure 11. Aplac model





Figure 12. Aplac parameters

aplacvar Ls 950pH					
aplacvar Rs 150m					
aplacvar Cext1 12pF	Dint1	Dext1	Dint2	Dext2	Dext3
aplacvar Cext2 14pF	BV=15	BV=15	BV=15	BV=15	BV=15
aplacvar Cext3 18pF	CJO=Cint1	CJO=Cext1	CJO=Cint2	CJO=Cext2	CJO=Cext3
aplacvar Cint1 4.5pF	IBV=1u	IBV=1u	IBV=1u	IBV=1u	IBV=1u
aplacvar Cint2 4pF	IKF=1000	IKF=1000	IKF=1000	IKF=1000	IKF=1000
aplacvar Rbump 17m	IS=10f	IS=10f	IS=10f	IS=10f	IS=10f
aplacvar Lbump 43pH	ISR=100p	ISR=100p	ISR=100p	ISR=100p	ISR=100p
aplacvar Rgnd 500m	N=1	N=1	N=1	N=1	N=1
aplacvar Lgnd 50pH	M=0.3333	M=0.3333	M=0.3333	M=0.3333	M=0.3333
aplacvar Cgnd 0.15pF	RS=0.29	RS=0.25	RS=0.31	RS=0.28	RS=0.25
aplacvar Rsub 100m	VJ=0.6	VJ=0.6	VJ=0.6	VJ=0.6	VJ=0.6
	TT=50n	TT=50n	TT=50n	TT=50n	TT=50n

3 Ordering information scheme

Figure 13. Ordering information scheme



4 Package information

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at www.st.com.

Figure 14. Package dimensions




Figure 15. Footprint




Figure 16. Marking





Figure 17. Flip Chip tape and reel specification



Note:

More information is available in the application notes:
AN2348: "STMicroelectronics 400 micro-metre Flip Chip: Package description and recommendation for use"
AN1751: "EMI Filters: Recommendations and measurements"

5 Ordering information

Table 3. Ordering information

Order code	Marking	Package	Weight	Base qty	Delivery mode
EMIF03-SIM02F3	HA	Flip Chip	1.74 mg	5000	Tape and reel 7"

6 Revision history

Table 4. Document revision history

Date	Revision	Changes
19-Jul-2005	1	Initial release.
26-Feb-2007	2	Changed out to ext in Configuration diagram on page 1. Added Ecopack statement. Reformatted to current layout standard. Updated Application note AN2348 reference and description.
28-Apr-2008	3	Updated ECOPACK statement. Updated Figure 13 , Figure 14 , and Figure 17 . Reformatted to current standards.

KTTIC

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED REPRESENTATIVE OF ST, ST PRODUCTS ARE NOT DESIGNED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS, WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2008 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

